



Hamburg - Germany

## Temporized wall mounted tap Art. Nr. 50033

Self closing wall mounted tap, 1/2" connection, with wall rosette. The body is made of chrome plated cast brass. Easy to install and specially designed to allow simple maintenance. **standard** cartridge with **prefixed** time from 3 to 25 seconds ( $\pm 10$  seconds). With this cartridge the time is pre-regulated as customers request with a delay time.

Here below you can find different options clearly explained:

### CHOICE OF FLOW DELAYS

A approx 3 sec.

B approx 4/6 sec. C approx 8/12 sec.

D approx 12/16 sec.

E approx 15/25 sec. standard or adjustable

**The self closing cartridges can be supplied with A flow rate regulation:**



	1	2	3	4
<b>BAR</b>	<b>L/M</b>	<b>L/M</b>	<b>L/M</b>	<b>L/M</b>
0.5	15	14.0	10.2	5.4
1	19.7	17.6	13.4	5.9
1.5	23.4	22.5	15.3	5.7
2	27	25.6	20.1	6.2
3	36	32.4	25	8.1

MINIMUM WORKING PRESSURE 0.1 BAR MAXIMUM WORKING PRESSURE 3 BAR.

### **ATTENTION:**

- + If the water pressure is above 4 bar, a pressure reducer is always recommended.
- + the good working of the tap is guaranteed when the water is without impurity. It is important to clean the supply pipes and to install a filter.
- + For changing the water flow, take off the cartridge from the body using a key Nr. 24, then you have to turn cup (F) on the crown ring (E), choosing flow requested from position 1 (Full Open) to position 4 ( Full Closed). Tightening torque of cartridge must be 12 Nm.

